



## Crystal Paints Paving Paint

Tough Polyurethane Semi-Gloss finish which repels water and oils. Suitable for interior and exterior concrete and timber surfaces including pathways, driveways, showrooms, patios, workshops, etc.

Application by brush or roller, if spraying follow with roller.

Recoat and walk on 30 mins – 3 hours depending on conditions.

Full Range of Colours and Sizes Available:

1lt \$28.88+gst

4lt \$73.50+gst

10lt \$159.75+gst

White

Black

Light Grey

Mid Grey

Charcoal

Monument

Safety Yellow

Sandstone

Light Ochre

Green

Blue

Red

**Before Painting:**

New concrete should be weathered for 2-3 months before painting.

Surfaces should be dry, dirt and dust free, grease, oils, polishes, and flaking paint removed.

**Instructions:**

- Clean concrete by acid etching it. To do this mix 1 part Hydrochloric acid to 1 part water and apply with a solvent resistant broom/brush. Allow an etching time of 1 hour. Use a mask, goggles, gloves, and footwear when using Hydrochloric Acid.
- Once the acid etch has finished bubbling, frothing, foaming etc the concrete will need to be high pressure cleaned afterwards. Make sure you remove all acid prior to applying paint as the paint will react to the acid.
- After the concrete has been cleaned and is dry you can apply your first coat of Paving Paint. For steep, very smooth or exterior surfaces Crystal Paints recommends using Crystal Paints Anti-Slip fine grit.
- Sprinkle the Anti-Slip grit on to your first coat of paint while it is still wet.
- When your first coat is dry (about 30mins-3hours after application) you can apply your second coat.
- Let your second coat cure for at least 24 hours before driving on it. Full curing time is up to 3 weeks.

**Additional Information:**

Coverage is 6 to 13 square metres per litre.

Wash up in mineral turpentine.

If you are going to spray, you may need to thin the paint with mineral turps depending on the spray unit.

This paint can be used on timber however the timber will require a primer or undercoat. We recommend Crystal Paints All Purpose Undercoat or Oil Based Timber Primer.

Bulk quantity

200 Litre drums, 1000 ICB



**FINNWAY AUSTRALIA PTY. LTD**

A.B.N. 52 008 183 855

Phone: (08) 8557 7811

[finnwaysales@aapt.net.au](mailto:finnwaysales@aapt.net.au)

Fax: (08) 8557 7311

[www.finnway.com.au](http://www.finnway.com.au)

